



Manage Centrally With No Additional Hardware Needed



AP One AX Lite comes equipped with InControl central management. Giving users the ability to control and monitor their network from any web browser. Manage network SSIDs, radio settings, and search event logs with ease to diagnose the entire network.

Turnkey or Custom Captive Portals



Wi-Fi Just Got Better

Integrated Wi-Fi 6 is 45% faster than the average Wi-Fi 5, has 4 more device capacity and consumes less power for connected devices.

Enterprise-Grade Roaming Speeds

Supports 802.11k/v/r, providing users a seamless roaming experience between access points.



Seamless Peplink SD-WAN Integration

Effortlessly integrate Peplink solutions with **AP One AX Lite** to provide unique network capabilities and network flexibility, making the whole experience more user friendly.

Centrally Managed with InControl

Monitor network health on a single dashboard. Push configuration profiles on multiple devices at once. Remotely access the Web Admin of any device.

Balance/MAX/FusionHub


Provides unbreakable connectivity by combining multiple WANs. Works with InControl to centralize VLAN, firewall, and outbound policies.

SD-Switch

Works with InControl to remotely configure and activate PoE ports. Monitor power consumption.

AP One

Works with InControl to centralize SSIDs, radio settings, and deliver captive portals.



AP One AX Lite





Specifications

Ethernet Ports 1 x 1 Gbps Gigabit Ethernet

Wi-Fi Standard Simultaneous

1 x 2.4GHz 802.11b/g/n/ax 1 x 5GHz 802.11a/n/ac/ax

Radio Chains/Streams 2 x 2:

Data Rates 2.4 GHz: up to 574 Mbps 5 GHz: up to 1200 Mbps

Channel Width 20/40/80 MHz

Recommended clients per Radio 256

SSID Per Radio 16

Transmit Power 2412 – 2472 MHz: 24dBm 5180 – 5825 MHz: 25dBm

Antenna Built-in Omni antenna: 2 x 3dBi - 2.4GHz

2 x 3dBi - 2.4GHz 2 x 3dBi - 5GHz

Enclosure Plenum-rated enclosure

Dimensions 5.9 x 5.9 x 1.3 inches 160 x 160 x 33 mm

Weight 0.84 pounds / 382 grams

Power Input 12V DC Jack

(Plug 5.5 x 2.1 mm, center positive)*

802.3at PoE*

Power Consumption14.5W (max.)Operating Temperature $32^{\circ}F - 104^{\circ}F$
 $0^{\circ}C - 40^{\circ}C$

Certifications FCC, CE, RoHS

Warranty 1 Year Limited Warranty

Network	Bridge Mode
	Router (NAT) Mode

Mesh Wireless Distribution System (WDS)

Support for PPPoE, Static IP, DHCP Management VLAN

Radio Multiple SSID

Auto Channel Selection Transmit Power Adjustment Neighbor AP Detection

Spanning Tree Protocol

AP Security Open

WPA/WPA2/WPA3-Personal WPA/WPA2-Enterprise

Device ManagementWeb Administrative Interface

InControl Cloud Management Peplink AP Controller SNMP v1, v2c and v3

Client Management Per SSID

VLAN with QoS (802.1p/802.1q) Bandwidth Control MAC Address Filtering Layer 2 Client Isolation Limit on Max. Number of Clients

Per Client

VLAN with RADIUS VLAN with VLAN Pool Bandwidth Control Multicast Filter

IGMP Snooping/Multicast Enhancement

Captive Portal by InControl

Package Contents AP One AX Lite,

Ceiling Mount Base (9/16" T-Rail), Ceiling Mount Base (15/16" T-Rail),

Mounting Screw Set

Ordering information

Product Code	Description
APO-AX-LITE	2 x 2 MU-MIMO Wi-Fi 6 AP for business, manageable by InControl. Simultaneous Dual-Band 802.11ax/ac/b/g/n

Feature Add-on

Product Code	Description
ACW-107	802.3af/at PoE Injector. Compatible with MAX Hotspot and AP One AX Series
ACW-602	1x12V3A Power Supply. Compatible with MAX HD2 and AP One AX Series



 $[\]ensuremath{^{\star}}$ AC/DC adapter and PoE Injector are not included.